

Colour Developer Replenisher C-41 CD-LR

Description :






- developer for the C-41 process with low replenishment rate (- 50 %);
- recommended for developing machines with high film utilization;
- reduced overflow - lower costs;- three-part;

Technical Data :

Processing Time : 3 min 15 s
 Temperature : 37,8 +/- 0,2°C
 Replenishment Rate : 22,5 ml / film 135-24

Mix Instructions :

preparation developer - replenisher :

Water (20-40 °C)	Part A	Part B	Part C	fill up with Water to
				
4 l	500ml	50 ml	250 ml	5 l
8 l	1 l	100 ml	500 ml	10 l
40 l	5 l	500 ml	2,5 l	50 l

preparation developer - working solution :

Replenisher	Starter Conc. C-41 CD-S	fill up with Water to
770 ml	48 ml	1000 ml

Colour Developer Replenisher C-41 CD-LR

Assortment:

Order Number	Product Name	Mix Size for	Concentrate	Capacity Films 135-24
13210	C-41 CD-LR	4 x 10 l	Part A 4 x 1,00l Part B 4 x 0,10l Part C 4 x 0,50l	1777
13212		2 x 50 l	Part A 2 x 5,00l Part B 2 x 0,50l Part C 2 x 2,50l	4444
13213		4 x 5 l	Part A 4 x 0,50l Part B 4 x 0,05l Part C 4 x 0,25l	888